

Technical sheet :

1950RT



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Imperial
Operating Weight		8400 lb
Unladen weight		7544 lb
Operating Capacity At 50% Tipping Load		2787 lb
Tipping capacity		5571 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	158 in
Height to Hinge Pin - Fully Raised	h28	120 in
Dump reach - Full height	r6	26 in
Dump angle at full height	a5	39 °
Overall length with bucket	l16	129 in
Departure angle	a2	27 °
Ground clearance	m4	7 in
Overall width less bucket	b1	69 in
Bucket Width	e1	70 in
Clearance Radius - Front with Bucket	b18	81 in
Engine		
Engine brand		Yanmar
Engine model		4TNV98C-NMS2V
Engine power (Hp)		69 Hp
Engine power (kW)		51.70 kW
Max. torque / Engine rotation		178 ft/lbs @ 2500 rpm
Battery voltage		12 V
Accessory plug		120 V
Alternator - Ampere		100 A
Transmission		
Transmission type		Hydrostatic
Hydraulics		
Standard flow - Auxiliary hydraulics		18 US gpm
Auxiliary Hydraulic Pressure		3249 PSI
High-Flow Auxiliary Hydraulics - Option		32 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		2901 PSI
Tank capacities		
Hydraulic tank capacity		10 US gal
Fuel tank capacity		16 US gal
Cooling liquid		3 US gal
Displacement / Number of cylinders		0.87 US gal / 4
Noise and vibration		
Noise to environment (LwA)		101.40 dB
Noise at driving position (LpA)		82 dB
Whole-Body Vibration (ISO 2631-1)		4 ft/s²